



EZ Series Phenol Analysers

The EZ Series Online Analysers offer an option to monitor Phenol in water. Typical applications are wastewater, drinking water, surface water.

The EZ1030 Analysers use colorimetric analysis to measure Phenol:

Standard measuring range: 0 - 2 mg/L

Options:

- Calibration to 10, 25, or 50% of standard range
- Internal dilution
- Multiple stream analysis (1-8 streams) reducing cost per sampling point
- Analogue and/or digital outputs for communication

Some applications may require the use of a sampling/filtration or an external dilution system for sample preconditioning. For this option please check the EZ9000 Sample preconditioning page.

Need support or a different configuration? Please contact us.

Part Number	Product description	Parameter	Measuring range	Output	GBP Price
EZ1030.99001C02	EZ1030 Phenol Analyser, 1 stream, Modbus RS485	Phenol	0 - 2 mg/L Phenol	Modbus RS485	Contact Us
			Optional:	Optional:	
			0 - 0.2 mg/L	Active 4 - 20 mA max.	
			0 - 0.5 mg/L	500 Ohm load, 1 to 8 outputs	
			0 - 1 mg/L	RS232, Modbus TCP/IP	
			0 - 8 mg/L (with internal dilution)		
			0 - 16 mg/L (with internal dilution)		
			0 - 200 mg/L (with internal dilution)		